



Emergency Battery Backup

Sump Pump System

Link₂O™ Remote Monitoring

Constantly monitors system conditions, and alerts you (by cellphone or computer) when your basement is in danger of flooding. At home, at work, or across the globe – you are protected and informed.

Proprietary Smart Charging Technology

Recharges battery 25% faster and extends battery life.

High Performance Pump

Removes up to 83% more gallons per charge than the leading competitor.



LEARN MORE AT:
www.mylink2o.com



12V 2700 GPH FPDC30

| PERFORMANCE (GPH) | | | | | | SOLIDS HANDLING |
|--------------------------------------|------|------|------|-----|-----------|-----------------|
| DISCHARGE HEIGHT ABOVE PUMPING LEVEL | 0' | 5' | 10' | 14' | MAX. LIFT | |
| FPDC30 | 2700 | 2040 | 1260 | 360 | 15' | 3/16" |

| FEATURE | FLOTEC® FPDC30 | COMPETITION | FLOTEC ADVANTAGE |
|-------------------------------|----------------|-------------|-----------------------------|
| Max Flow (12.7V) | 2700 | 2200 | 22% more flow |
| Flow @ 10' (12.7V) | 1260 | 900 | 40% more flow |
| Max Head | 15' | 14' | 7% higher head |
| Gallons per charge @ 10' head | 11,500 | 6300 | 83% more gallons per charge |
| Charger | 2.0 AMPS | 1.6 AMPS | 25% faster charging |

*Performance data based on internal testing using BAT75

| MODEL | WARRANTY | UPC | CARTON DIMENSIONS | PALLET QTY. | WEIGHT |
|---------------|----------|--------------|-----------------------|-------------|-----------|
| FPDC30 | 2 YEAR | 022315368385 | 18.25 x 10.13 x 16.63 | 20 | 12.2 LBS. |



Includes: battery case control unit, 12V pump, reed switch, AC power supply, wireless gateway, 1-1/4" NPT to 1-1/2" glue PVC elbow

Compatible with flooded and sealed AGM deep cycle lead acid batteries.

For best performance use Flotec BAT40 or BAT75 sealed AGM batteries.

293 Wright Street, Delavan, WI 53115
For Questions or Installation Instructions:
www.flotecwater.com 1-800-365-6832